US Army Corps
of Engineers
Hydrologic Engineering Center

AD-A236 925

Predicting Deposition Patterns in Small Basins



Technical Paper No. 133
March 1991

Approved for Public Release. Distribution is Unlimited.

91-02392

91 6 17 081

Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution within the Corps of Engineers.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

PREDICTING DEPOSITION PATTERNS IN SMALL BASINS[1]

By D. Michael Gee, Research Hydraulic Engineer, Hydrologic Engineering Center, Davis, CA.

ABSTRACT

A technique for estimating sediment depositional patterns based upon flow patterns is described. Flow patterns are computed using a finite element model for two-dimensional, vertically averaged flow. Once the velocity and depth fields are computed, the bed shear stress distribution can be found. If the annual volume and approximate particle size of the inflowing load is known, anticipated depositional locations and quantities can then be estimated. Use of this technique to forecast the temporal development of the deposits by computing the velocity fields for several steady flow conditions is described. The resulting graphical displays of velocity fields and shear stress contours are very useful to the design engineer. This procedure avoids the complexity associated with use of a two-dimensional sediment transport and dispersion model. Application of the technique to the design of a basin 180 ft. (55 m.) wide by 610 ft. (186 m.) long is described.

INTRODUCTION

Conventional sediment basin design procedures rely on volumetric relationships to determine flow through times, estimated trap efficiency, and average annual deposition rates. Design guidance has been prepared by USACE (1989). These approaches do not necessarily reflect the interaction between changes in bed topography due to scour and/or deposition and the influence of these changes on velocity and shear stress distributions. Some designs have been approached using one-dimensional numerical modeling of flow and sediment such as HEC-6 (USACE-HEC, 1990). Some concerns with these approaches are that complex velocity patterns such as recirculation and short circuiting may not be properly described. These flow patterns may result in uneven distributions of sediment concentration and, therefore, an uneven distribution of sediment deposits (Montgomery, et al. 1983). The use of a fully two-dimensional model for both flow and sediment distribution such as TABS-2 (McAnally et al. 1984) is an attractive approach to improve the prediction of the distribution of sediment deposits. The use of such a model, however, may involve more effort and data acquisition than can be justified for small basin design. The technique described herein represents a midway approach that includes the velocity and shear stress fields in detail, from which the sediment deposition distribution and rates can be inferred. A brief description of this approach was presented by Deering and Larock (1989).

MODEL SELECTION

It is assumed that the salient flow features of small basins can be described in the two horizontal directions and that the variance of velocity in the vertical is the traditional logarithmic velocity distribution for turbulent flow in open channels (French 1985). A widely used model that is suitable for this condition is RMA-2 (King & Norton 1978). RMA-2 has been applied to a wide variety of problems including floodplain analysis (Gee et al. 1990), marsh flooding (MacArthur et al. 1990), sediment basin design (Deering & Larock 1989), has been adapted for bridge design (FHWA 1989), and serves as the hydrodynamic module of the TABS-2 system (McAnally et al. 1984). This model solves the depth integrated Reynolds equations for two-dimensional free-surface flow in the horizontal plane using the finite element method for both steady and unsteady flows. The finite element

[1]Presented at the Fifth Federal Interagency Sedimentation Conference, Las Vegas, Nevada, March 1991.

formulation of RMA-2 allows boundary roughness and geometric resolution to vary spatially to accurately depict topography. It also provides a wide variety of boundary conditions. Wetting and drying of portions of the solution domain is allowed. The two-dimensional approach relieves the engineer from having to construct cross sections that are perpendicular to the flow for all flows, as is required in a one-dimensional analysis.



Figure 1. Example Finite Element Mesh, Wildcat Creek Basin.

APPROACH

An example finite element mesh is shown in Fig. 1. Note that the elements are both quadrilateral and triangular. Computational nodes exist at the corners and mid-sides of each element. The bottom elevation is given at each corner node and linearly interpolated for the mid-side nodes. Bed roughness and turbulent exchange coefficients are assigned to groups of elements (not necessarily neighbors) by the user. Solution of the two-dimensional flow equations provides the x- and y-components of the velocity, and the depth, at each computational node. The local shear stress can be calculated from these variables if one assumes that the relation for average shear in a cross section can be applied locally as follows.

$$\tau = \gamma RS \tag{1}$$

Where τ is the bed shear stress, γ is the unit weight of water, R is the hydraulic radius (taken here as the local nodal depth) and S is the friction slope. Now, rewriting Manning's equation in terms of S, we have:

$$S = \frac{n^2 u^2}{2.22 R^{4/3}} \quad (2)$$

Where u is the resultant of the calculated x and y nodal velocity components, as shown in equation (3) and n is Manning's roughness coefficient.

$$u^2 = u_x^2 + u_y^2 \quad (3)$$

Combining, we can solve for the shear stress:

$$\tau = \gamma \frac{n^2 u^2}{2.22 R^{1/3}} \quad (4)$$

One must now relate the n-values, which are associated with elements, with the computed values for u and R (depth) which are located at nodes. For this study, the n-value associated with a node was computed as the arithmetic average of the n-values for all elements connected to that node. We have placed these computations in the vector plotting program (VECTOR) which is a post-processor for RMA-2. VECTOR also prepares files of water surface elevation and velocity magnitude for contouring.

AN EXAMPLE

Introduction

The Wildcat Creek sediment basin was designed to trap sediment that potentially could cause excess scour or deposition in a downstream flood control channel. Right-of-way considerations and environmental concerns dictated the bent alignment shown in Fig. 1 (flow is from right to left). Based on cross section average velocity and settling lengths computed from the particle fall velocity, it was estimated that the basin would trap 100% of the sediment larger than fine sand (0.125 mm). A hydrodynamic analysis was performed to ascertain whether the bent alignment would indeed trap the size range and volume of sediment needed and whether high velocities would impinge on the banks requiring some form of bank protection.

Sediment Basin Description

The Wildcat Creek sediment basin was designed to have a maximum width of 180 ft. (55 m.) and length of 610 ft. (186 m.). The bottom slope is 0.0005 and the side slopes 1V:3H. The maximum depth is about 12 ft. (3.7 m.).

Hydraulics

As Wildcat Creek is ephemeral, continuous simulation was not necessary. Therefore, several hydraulic scenarios were studied to verify that the basin would perform as designed. It was planned that deposits would most likely have to be removed from the basin on an annual basis. This led to simplification in the number of conditions to be analyzed because the problem was reduced to

evaluation of the interactions between average annual deposition and the occurrence of the design (1% exceedance) event. The results presented here are only for the design event; refer to Deering and Larock (1989) for information on other scenarios. Furthermore, as the basin volume is small relative to the hydrograph volume, the analysis could be performed assuming steady flow. The 1% chance exceedance event is 2300 cfs (65 cms). The drainage area is about 7.8 mi^2 (2000 hectares).

Scenario

The situation presented herein represents the condition of the basin after several years' average annual deposition (not removed). The flow evaluated is that of the design (1% chance exceedance) event. The distribution of the deposits shown in Fig. 2 was created based on simulation of the shear stress distribution in the empty basin and observation of other flood control projects having similar flow and sediment transport conditions. The bar deposits are formed from flows expanding into open areas. Initial deposits will form in the lower velocity areas causing the flow to redistribute, expanding again and reinitiating the bar formation process. This results in bar formation on the left and right banks, immediately downstream of the entrance, and a central bar further downstream. The assumed deposition pattern has a volume equivalent to that of the average annual deposits for the time period selected. The nodal elevations of the finite element mesh that was developed for the design (empty) basin were modified to reflect this hypothetical deposition pattern.

Modeling parameters

The Manning's n-values were set to 0.03 for most of the basin based on it being maintained as smooth earth. The values for one portion of the left bank were set to 0.06 based on maintaining the native heavy vegetation there. The sensitivity of the results to these values, assuming the project is

Figure 2. Bottom Elevations (ft).



not well maintained should be checked and may be significant to the design event water surface

elevation. The turbulent exchange coefficients were uniformly set to 10 lb-sec/ft^2 (480 N-sec/m^2) for all elements. This was based on prior experience with finite element meshes of this scale. The sensitivity of the results to variation of these values within reasonable ranges was checked and found to be insignificant.

Boundary conditions

This is a simple 2-D problem in that it is analogous to traditional 1-D backwater computations with regard to boundary conditions. A discharge was specified at the upstream (right) end of the model. In 2-D, however, the direction of the discharge must be given which was selected to be perpendicular to the inflow boundary line (see Fig. 3). The downstream boundary condition was specified as a water surface elevation appropriate for the discharge being analyzed based on design studies of the downstream reach. A rating curve could have been used for the downstream boundary if appropriate. Along all other boundaries, the flow direction is parallel to the boundary.



Figure 3. Velocity Field with Possible Bar Configuration. Q=2300 cfs.

Modeling results

The flow field for the design event is depicted on Figure 3. The flow enters the basin as a plume of relatively high velocity. Recirculation zones are seen on each side of the inflow plume. This is obviously not a one-dimensional situation. The hypothetical bar formations do not appear to force the higher velocity jet against either of the banks as originally suspected. The associated shear stress field for this flow and bottom condition is shown in Figure 4.

The shear stress is low enough that sediments of the size of interest will be trapped in the basin. Note particularly the zones of near zero shear that correspond to the recirculation cells near the left and right banks. The clustering of contours near the banks is an artifact of the contouring process.



Figure 4. Shear Stress (lb/sq ft).

CONCLUSIONS

The technique presented herein represents a midway approach to the prediction of spatially complex sediment transport processes. Much can be inferred from viewing the velocity and shear stress distributions. Once the velocity field has been computed, the computation of the shear stress distribution is trivial. If, at this stage, one determines that simulation of the full two-dimensional transport and dispersion of sediment is necessary, the hydrodynamic analysis already performed can be used directly in the sediment transport simulation.

COMPUTATIONAL ASPECTS

The finite element mesh used for this study contains about 550 elements and 1370 nodes. This produces about 2300 simultaneous equations. To solve this system for steady flow using six iterations takes about 15 minutes on a 25 MHz 386 computer. The system can be run within the DOS 640K limitation.

ACKNOWLEDGEMENTS

This study was performed for the U. S. Army Corps of Engineers District, Sacramento with the assistance of the U. S. Army Corps of Engineers Waterways Experiment Station. The opinions expressed herein are those of the author and not necessarily those of the U. S. Army Corps of Engineers.

REFERENCES

Deering, M. K. and Larock, B. E. (1989) "The Design of Sediment Basins Using Two-Dimensional Hydrodynamic Techniques," Proceedings of the 1989 ASCE National Conference on Hydraulic Engineering, New Orleans, LA.

Federal Highway Administration (1989) "FESWMS-2DH Finite Element Surface-Water Modeling System: Two-Dimensional Flow in a Horizontal Plane," Pub. No. FHWA-RD-88-177.

French, R. H. (1985) "Open-Channel Hydraulics," McGraw-Hill.

Gee, D. M., et al. (1990) "Two-Dimensional Floodplain Modeling," Proceedings of the 1990 ASCE National Conference on Hydraulic Engineering and the International Symposium on the Hydraulics/Hydrology of Arid Lands, San Diego, CA.

King, I. P. and Norton, W. R. (1978) "Recent Application of RMA's Finite Element Models for Two-Dimensional Hydrodynamics and Water Quality," Proceedings of the 2nd. Int. Conf. on Finite Elements in Water Resources, Pentech Press, London.

MacArthur, R. C., et al. (1990) "Two-Dimensional Finite Element Simulation of the Flooding Characteristics in Kawainui Marsh, Hawaii, "Proceedings of the 1990 ASCE National Conference on Hydraulic Engineering and the International Symposium on the Hydraulics/Hydrology of Arid Lands, San Diego, CA.

McAnally, W. H., et al. (1984) "Application of Columbia Hybrid Modeling System," Jour. Hyd. Engr., ASCE Vol. 110, No. 5, Paper 18796.

Montgomery, R. L., et al. (1983) " Dredged Material Sedimentation Basin Design," Jour. Env. Engineering, ASCE, Vol 109, No. 2.

U. S. Army Corps of Engineers (1989) "Sedimentation Investigations of Rivers and Reservoirs," Engineer Manual 1110-2-4000.

U. S. Army Corps of Engineers Hydrologic Engineering Center (1990) "HEC-6 Scour and Deposition in Rivers and Reservoirs," Users Manual.

TECHNICAL PAPER SERIES
($2.00 per paper)

TP-1 Use of Interrelated Records to Simulate Streamflow
TP-2 Optimization Techniques for Hydrologic Engineering
TP-3 Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs
TP-4 Functional Evaluation of a Water Resources System
TP-5 Streamflow Synthesis for Ungaged Rivers
TP-6 Simulation of Daily Streamflow
TP-7 Pilot Study for Storage Requirements for Low Flow Augmentation
TP-8 Worth of Streamflow Data for Project Design - A Pilot Study
TP-9 Economic Evaluation of Reservoir System Accomplishments
TP-10 Hydrologic Simulation in Water-Yield Analysis
TP-11 Survey of Programs for Water Surface Profiles
TP-12 Hypothetical Flood Computation for a Stream System
TP-13 Maximum Utilization of Scarce Data in Hydrologic Design
TP-14 Techniques for Evaluating Long-Term Reservoir Yields
TP-15 Hydrostatistics - Principles of Application
TP-16 A Hydrologic Water Resource System Modeling Techniques
TP-17 Hydrologic Engineering Techniques for Regional Water Resources Planning
TP-18 Estimating Monthly Streamflows Within a Region
TP-19 Suspended Sediment Discharge in Streams
TP-20 Computer Determination of Flow Through Bridges
TP-21 An Approach to Reservoir Temperature Analysis
TP-22 A Finite Difference Method for Analyzing Liquid Flow in Variably Saturated Porous Media
TP-23 Uses of Simulation in River Basin Planning
TP-24 Hydroelectric Power Analysis in Reservoir Systems
TP-25 Status of Water Resource Systems Analysis
TP-26 System Relationships for Panama Canal Water Supply
TP-27 System Analysis of the Panama Canal Water Supply
TP-28 Digital Simulation of an Existing Water Resources System
TP-29 Computer Applications in Continuing Education
TP-30 Drought Severity and Water Supply Dependability
TP-31 Development of System Operation Rules for an Existing System by Simulation
TP-32 Alternative Approaches to Water Resource System Simulation
TP-33 System Simulation for Integrated Use of Hydroelectric and Thermal Power Generation
TP-34 Optimizing Flood Control Allocation for a Multipurpose Reservoir
TP-35 Computer Models for Rainfall-Runoff and River Hydraulic Analysis
TP-36 Evaluation of Drought Effects at Lake Atitlan
TP-37 Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes
TP-38 Water Quality Evaluation of Aquatic Systems
TP-39 A Method for Analyzing Effects of Dam Failures in Design Studies
TP-40 Storm Drainage and Urban Region Flood Control Planning
TP-41 HEC-5C, A Simulation Model for System Formulation and Evaluation
TP-42 Optimal Sizing of Urban Flood Control Systems
TP-43 Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems
TP-44 Sizing Flood Control Reservoir Systems by Systemsm Analysis
TP-45 Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin
TP-46 Spatial Data Analysis of Nonstructural Measures
TP-47 Comprehensive Flood Plain Studies Using Spatial Data Management Techniques
TP-48 Direct Runoff Hydrograph Parameters Versus Urbanization
TP-49 Experience of HEC in Disseminating Information on Hydrological Models
TP-50 Effects of Dam Removal: An Approach to Sedimentation
TP-51 Design of Flood Control Improvements by Systems Analysis: A Case Study
TP-52 Potential Use of Digital Computer Ground Water Models
TP-53 Development of Generalized Free Surface Flow Models Using Finite Element Techniques
TP-54 Adjustment of Peak Discharge Rates for Urbanization
TP-55 The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers
TP-56 Experiences of the Hydrologic Engineering Center in Maintaining Widely Used Hydrologic and Water Resource Computer Models
TP-57 Flood Damage Assessments Using Spatial Data Management Techniques
TP-58 A Model for Evaluating Runoff-Quality in Metropolitan Master Planning
TP-59 Testing of Several Runoff Models on an Urban Watershed
TP-60 Operational Simulation of a Reservoir System with Pumped Storage
TP-61 Technical Factors in Small Hydropower Planning
TP-62 Flood Hydrograph and Peak Flow Frequency Analysis
TP-63 HEC Contribution to Reservoir System Operation
TP-64 Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study
TP-65 Feasibility Analysis in Small Hydropower Planning
TP-66 Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems
TP-67 Hydrologic Land Use Classification Using LANDSAT
TP-68 Interactive Nonstructural Flood-Control Planning
TP-69 Critical Water Surface by Minimum Specific Energy Using the Parabolic Method
TP-70 Corps of Engineers Experience with Automatic Calibration of a Precipitation-Runoff Model

TP-71 Determination of Land Use from Satellite Imagery for Input to Hydrologic Models
TP-72 Application of the Finite Element Method to Vertically Stratified Hydrodynamic Flow and Water Quality
TP-73 Flood Mitigation Planning Using HEC-SAM
TP-74 Hydrographs by Single Linear Reservoir Model
TP-75 HEC Activities in Reservoir Analysis
TP-76 Institutional Support of Water Resource Models
TP-77 Investigation of Soil Conservation Service Urban Hydrology Techniques
TP-78 Potential for Increasing the Output of Existing Hydroelectric Plants
TP-79 Potential Energy and Capacity Gains from Flood Control Storage Reallocation at Existing U. S. Hydropower Reservoirs
TP-80 Use of Non-Sequential Techniques in the Analysis of Power Potential at Storage Projects
TP-81 Data Management Systems for Water Resources Planning
TP-82 The New HEC-1 Flood Hydrograph Package
TP-83 River and Reservoir Systems Water Quality Modeling Capability
TP-84 Generalized Real-Time Flood Control System Model
TP-85 Operation Policy Analysis: Sam Rayburn Reservoir
TP-86 Training the Practitioner: The Hydrologic Engineering Center Program
TP-87 Documentation Needs for Water Resources Models
TP-88 Reservoir System Regulation for Water Quality Control
TP-89 A Software System to Aid in Making Real-Time Water Control Decisions
TP-90 Calibration, Verification and Application of a Two-Dimensional Flow Model
TP-91 HEC Software Development and Support
TP-92 Hydrologic Engineering Center Planning Models
TP-93 Flood Routing Through a Flat, Complex Flood Plain Using a One-Dimensional Unsteady Flow Computer Program
TP-94 Dredged-Material Disposal Management Model
TP-95 Infiltration and Soil Moisture Redistribution in HEC-1
TP-96 The Hydrologic Engineering Center Experience in Nonstructural Planning
TP-97 Prediction of the Effects of a Flood Control Project on a Meandering Stream
TP-98 Evolution in Computer Programs Causes Evolution in Training Needs: The Hydrologic Engineering Center Experience
TP-99 Reservoir System Analysis for Water Quality
TP-100 Probable Maximum Flood Estimation - Eastern United States
TP-101 Use of Computer Program HEC-5 for Water Supply Analysis
TP-102 Role of Calibration in the Application of HEC-6
TP-103 Engineering and Economic Considerations in Formulating
TP-104 Modeling Water Resources Systems for Water Quality
TP-105 Use of a Two-Dimensional Flow Model to Quantify Aquatic Habitat
TP-106 Flood-Runoff Forecasting with HEC-1F
TP-107 Dredged-Material Disposal System Capacity Expansion
TP-108 Role of Small Computers in Two-Dimensional Flow Modeling
TP-109 One-Dimensional Model For Mud Flows
TP-110 Subdivision Froude Number
TP-111 HEC-5Q: System Water Quality Modeling
TP-112 New Developments in HEC Programs for Flood Control
TP-113 Modeling and Managing Water Resource Systems for Water Quality
TP-114 Accuracy of Computed Water Surface Profiles - Executive Summary
TP-115 Application of Spatial-Data Management Techniques in Corps Planning
TP-116 The HEC's Activities in Watershed Modeling
TP-117 HEC-1 and HEC-2 Applications on the MicroComputer
TP-118 Real-Time Snow Simulation Model for the Monongahela River Basin
TP-119 Multi-Purpose, Multi-Reservoir Simulation on a PC
TP-120 Technology Transfer of Corps' Hydrologic Models
TP-121 Development, Calibration and Application of Runoff Forecasting Models for the Allegheny River Basin
TP-122 The Estimation of Rainfall for Flood Forecasting Using Radar and Rain Gage Data
TP-123 Developing and Managing a Comprehensive Reservoir Analysis Model
TP-124 Review of the U.S. Army Corps of Engineering Involvement With Alluvial Fan Flooding Problems
TP-125 An Integrated Software Package for Flood Damage Analysis
TP-126 The Value and Depreciation of Existing Facilities: The Case of Reservoirs
TP-127 Floodplain-Management Plan Enumeration
TP-128 Two-Dimensional Floodplain Modeling
TP-129 Status and New Capabilities of Computer Program HEC-6: "Scour and Deposition in Rivers and Reservoirs"
TP-130 Estimating Sediment Delivery and Yield on Alluvial Fans
TP-131 Hydrologic Aspects of Flood Warning - Preparedness Programs
TP-132 Twenty-five Years of Developing, Distributing, and Supporting Hydrologic Engineering Computer Programs
TP-133 Predicting Deposition Patterns in Small Basins

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	1b. RESTRICTIVE MARKINGS
2a. SECURITY CLASSIFICATION AUTHORITY	3. DISTRIBUTION/AVAILABILITY OF REPORT
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE	
4. PERFORMING ORGANIZATION REPORT NUMBER(S) Technical Paper No. 133	5. MONITORING ORGANIZATION REPORT NUMBER(S)
6a. NAME OF PERFORMING ORGANIZATION Hydrologic Engineering Center 6b. OFFICE SYMBOL (If applicable) CEWRC-HEC	7a. NAME OF MONITORING ORGANIZATION U.S. Army Corps of Engineers Water Resources Support Center
6c. ADDRESS (City, State, and ZIP Code) 609 Second Street Davis, California 95616	7b. ADDRESS (City, State, and ZIP Code) Casey Building #2594 Fort Belvoir, Virginia 22060
8a. NAME OF FUNDING/SPONSORING ORGANIZATION 8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER
8c. ADDRESS (City, State, and ZIP Code)	10. SOURCE OF FUNDING NUMBERS PROGRAM ELEMENT NO. / PROJECT NO. / TASK NO. / WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) Predicting Deposition Patterns in Small Basins	
12. PERSONAL AUTHOR(S) D. Michael Gee	
13a. TYPE OF REPORT Technical Paper 13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) March 1991 15. PAGE COUNT 7
16. SUPPLEMENTARY NOTATION	
17. COSATI CODES FIELD / GROUP / SUB-GROUP	18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) Two-dimensional Flow, Finite Elements, Sediment Transport Modeling

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

A technique for estimating sediment depositional patterns based upon flow patterns is described. Flow patterns are computed using a finite element model for two-dimensional, vertically averaged flow. Once the velocity and depth fields are computed, the bed shear stress distribution can be found. If the annual volume and approximate particle size of the inflowing load is known, anticipated depositional locations and quantities can then be estimated. Use of this technique to forecast the temporal development of the deposits by computing the velocity fields for several steady flow conditions is described. The resulting graphical displays of velocity fields and shear stress contours are very useful to the design engineer. This procedure avoids the complexity associated with use of a two-dimensional sediment transport and dispersion model. Application of the technique to the design of a basin 180 ft. (55 m.) wide by 610 ft. (186 m.) long is described.

20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS	21. ABSTRACT SECURITY CLASSIFICATION
22a. NAME OF RESPONSIBLE INDIVIDUAL Darryl W. Davis, Director, HEC	22b. TELEPHONE (Include Area Code) (916) 756-1104 22c. OFFICE SYMBOL CEWRC-HEC

DD Form 1473, JUN 86 *Previous editions are obsolete.*

SECURITY CLASSIFICATION OF THIS PAGE
UNCLASSIFIED